

MSiA Seminar Series

From Anomaly Detection to Data Visualization: In the Trenches of the CTIO's Office


Christopher Laporte February 26, 2019




Copyright 2019 California Institute of Technology. U.S. Government sponsorship acknowledged


- JPL
- Data Science @ JPL
- Case Projects
- Wrap-up
- Q/A


1. JPL

















Snapshot

- Over 45 current (in-flight) missions
- Over 15 future missions currently in development
- Operates the Deep Space Network (DSN)
- Scope and volume of scientific data is large (NISAR will produce 3-5 TB daily)




A single DSN 70-meter radio antenna in Goldstone, CA

How can we as data scientists aid JPL in its mission?

2. Data Science @ JPL

Business IT Data Science






Business IT Data Science: Sample Projects


Q: How can we improve Early Career Hire retention?




Q: How many tickets should we release for Explore JPL and how should we allocate the tickets throughout the day?



Q: Which schools provide us with the most successful employees?



Q: How can we reduce conference travel expenses?



Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California

Institute of Technology.



Chief Technology and Innovation Office

- Collection of data scientists, cloud engineers, software developers, and data visualization gurus
- Infuse new technologies and techniques into the way we do things at JPL
- Automated intelligence, digital transformation, unstructured information management, open source, cyber security, chatbots, IoT, next-gen robotics and flight hardware






How We Work

- Talk to everyone and build trust
- Identify and seize moments of engagement with passionate end-users
- Rapidly prototype and iterate
- Focus on the user experience

Engineering Data Management Initiative


What do our employees do?

 Classify JPL Roles using clickstream data from a variety of tools



Foundry Data Science

- A-team studies: Early stage mission formulation and feasibility assessment
- Need to know who to include (SMEs), what historical information is available
- A-team tool



Problem Reporting System

- Henosis: A python framework for deploying recommendation models for form fields
 - Open Issues! https://github.com/vc1492a/henosis/issues
- Identifying minority class labels from limited training data
 - Ex: spacecraft safings, escapes

JPL Open Source Rover


- DIY Rover you can build at home
- https://opensourcerover.jpl.nasa.gov/





Rover Drive-By Science


- Current major bottleneck for AI on rovers: extremely limited on-board computation resources
- What would high performance spacecraft computing enable for future missions?



Comic by PI Hiro Ono detailing the "Unnoticed Green Monster Problem" (UGMP)

Data-Driven Discovery of Models (DARPA)


- Automate the development of machine learning pipelines
- Allow SMEs to analyze data without the need for a data scientist
- Architecting and implementing a library of ML primitives
- Facilitating and cooperation and collaboration between the 23 performers



Active Social Engineering Defense (DARPA)

- Proactively respond to social engineering attacks (eg, phishing emails) with chatbots
- Identify and engage attacks, eventually turning them over to law enforcement
- Develop a test environment that will utilize JPL's email system and evaluation methodologies for the performers

Cyber Security Data Wall




And much more...

- Small satellite data science
- Cloud engineering
- Next-gen flight hardware/robotics
- MGSS (multi-mission ground systems and services) open source policy
- Intelligent assistants/chatbots

3. Case Project: Cyber Security Visualization

Snapshot

- ~ 330,000 events are observed by our firewall... every minute...
 after filtering
- Use a host of 3rd party software/tools to help monitor network
- Even after best filtering attempts, security engineers are still left with ~650 potential threats to review / day
- Cost of a single successful attack could be astronomical



Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California


Institute of Technology.

DEMO

3. Case Project: Telemetry Anomaly Detection

Motivation

- Thresholding, expert systems
 - Reliance on expert knowledge
 - Custom
 - Not complete
 - Accuracy
 - Appropriate limits change
- Increasing data rates
 - SWOT, NISAR = 3-5 TB daily
- Smaller missions (e.g. cubesats)
 - Less people for ops



Simple example of anomaly that would be undetected by a threshold

~40% of anomalies in experiments are of this nature

- High volumes of testbed data
- Investigative aspect
 - Focused, prioritized telemetry review
 - Help with causal fault analysis
 - What anomalies were detected leading up to a failure?


Anomaly Categories


Chandola et al. 2007

Point

Contextual

Collective (sequential)






- Use Recurrent Neural Networks (LSTMs) to predict incoming telemetry values using recent telemetry, commands, and event records (EVRs) as inputs
- Where predictions are substantially different from actual telemetry values, these are identified as potentially anomalous events
 - Novel method for defining "substantially different"
- https://www.kdd.org/kdd2018/accepted-papers/view/detecting-spacecraft-anomalies-using-lstmsand-nonparametric-dynamic-thresh

Single-Channel Prediction

Reconstruction Errors

Actuals and Prediction


Raw Reconstruction Error



Dynamic Anomaly Threshold

Anomalous






Dynamic Anomaly Threshold

Nominal

Reconstruction Error



Dynamic Anomaly Threshold

$$\mathbf{e}_s = [e_s^{(t-h)}, \dots, e_s^{(t-l_s)}, \dots, e_s^{(t-1)}, e_s^{(t)}]$$

$$\boldsymbol{\epsilon} = \mu(\mathbf{e}_s) + \mathbf{z}\sigma(\mathbf{e}_s)$$

$$\epsilon = argmax(\epsilon) = \frac{\Delta \mu(\mathbf{e}_s)/\mu(\mathbf{e}_s) + (\Delta \sigma(\mathbf{e}_s)/\sigma(\mathbf{e}_s)}{n(\mathbf{e}_a) + n(\mathbf{E}_{seq})^2}$$


$$\Delta\mu(\mathbf{e}_s) = \mu(\mathbf{e}_s) - \mu(\{e_s \in \mathbf{e}_s | e_s < \epsilon\})$$

$$\Delta\sigma(\mathbf{e}_s) = \sigma(\mathbf{e}_s) - \sigma(\{e_s \in \mathbf{e}_s | e_s < \epsilon\})$$

$$\mathbf{e}_a = \{e_s \in \mathbf{e}_s | e_s > \epsilon\}$$

$$\mathbf{E}_{seq} = \text{continuous sequences of } e_a \in \mathbf{e}_a$$

Experiments – Two Representative Spacecraft



Soil Moisture Active Passive (SMAP)

- Higher, more consistent data rates
- Fewer, more routine behaviors




Mars Science Laboratory (Curiosity or MSL)

- More channels (12k)
- Less data, less consistent delivery
- Extremely varied behaviors
 - Training on recent data isn't enough

Experiments – Incident Surprise, Anomaly Reports (ISAs)

- Scraped ISAs to find mentions of telemetry channels
 - Ex. "On DOY 192, in the time range from 09:21z through 10:47z, the following channels were found to have odd constant values: A-3, A-4, A-5, A-6, G-3"



- Labeled anomalous ranges for 112 unique ISA anomalies
- Significant portion of contextual anomalies (39%)

Validation: Predicting ISAs

- Identified all Incident, Surprise, Anomaly (ISA) reports that were apparent in telemetry (EHA) for SMAP and MSL
- Ran Telemanom system over time period surrounding each ISA to see if system would have detected the anomaly



Results

Thresholding Approach	Precision	Recall	$F_{0.5}$ score		Recall - point	Recall - contextual
Non-Parametric w/ Pruning $(p = 0.13)$				MSL	78.9%	58.8%
MSL	92.6%	69.4%	0.69	SMAP	95.3%	76.0%
SMAP	85.5%	85.5%	0.71	Total	90.3%	69.0%
Total	87.5%	80.0%	0.71			Contextual anomalies
	80% of all ISAs were identified (~115 in total)					are those that are not detectable by thresholds (0% recall)

Current Work: MSL

- Extending Telemanom to rovers/planetary missions
 - Prediction of telemetry is harder with more variety and irregularity of behaviors
 - Models need more training and detailed inputs surrounding commands and EVRs
- Early progress
 - Detected Martian sandstorm early with small number of Thermal channels
 - Achieving very high prediction accuracy for thermal channels (~98%)

Future Work

- Research new methods of dimensionality reduction for our EVR encoding
- Refactor code base to generalized and modular state
- Provide an API and frontend adjustments to allow for the training of multiple channels within a single LSTM
- Research and compare new modeling methods for time sequenced data

4. Wrap-up

Review: How We Work

- Talk to everyone and build trust
- Identify and seize moments of engagement with passionate end-users
- Rapidly prototype and iterate
- Focus on the user experience


Thanks

5. Q/A



jpl.nasa.gov

Formulation




h = historical window of errors ls = sequence length

Recurrent Neural Nets


- Memory (lossy summary)
- Parameter sharing
 - Extend model to apply to different lengths and generalize across time steps
 - Don't have to have separate parameters for each time value
- Recurrence
 - Always has same input size regardless of sequence length

$$m{h}^{(t)} = g^{(t)}(m{x}^{(t)}, m{x}^{(t-1)}, m{x}^{(t-2)}, \dots, m{x}^{(2)}, m{x}^{(1)})$$

= $f(m{h}^{(t-1)}, m{x}^{(t)}; m{ heta}).$



From RNNs to LSTMs (Goodfellow et. al, 2016)




Crucial addition (2000): Condition loop on context (with another hidden unit)


Ian Goodfellow, Yoshua Bengio, Aaron Courville, 2016. *Deep Learning*. MIT Press. http://deeplearningbook.org.

Initial Pilot: SMAP

- Deployed end-to-end autonomous system
- Monitored ~750 core telemetry channels from Aug 2017 – May 2018
 - Detected multiple verified anomalous events
 - Partial eclipse (Feb 15, 2018)
- Radar (HPA) failure investigation
 - Ran system ~2 months prior to failure, detected many of same telemetry oddities that were identified during peer review process following failure







Clicking and dragging across an **Interface: Drilldown** area allows for løóking down a level to channel groups with subsystems Thu 15 06 AM 09 AM 12 PM 03 PM Each row represents a group of channels and Thermal hovering shows the group name subsystem_group Ther al Fuel Tank & PDM Instrument Clicking takes the user into a similar view but in the next level down for the selected


window

Users can drill down into the raw **Interface: Drilldown (cont.)** telemetry for each channel (blue) and compare to the model SMAP VITALS SAVE CHANGES predictions (orange) Anomaly (anom15187563460001518758026000) changed to: ANOMALOUS Users can click to tag Channel Values 19,99611 anomalies as true or false Smoothed Error 0.06839 positives, which are used by the system to refine results True = green To get more details on False = gray channel history, users can go directly to the same view in Unlabeled = red visualization tools like SmapVitals 06 PM Where prediction errors are large, anomalies are flagged


02.26.19


jpl.nasa.gov

Results




Not Gaussian





p-value in normal test: 1.17603615763e-237


Pruning



$$\mathbf{e}_{max} = [0.01396, 0.01072, 0.00994]$$

$$p = 0.1$$

Foundation



Deployed in AWS GovCloud Sandbox **System Architecture GPU** jupyter Telemetry ** Elasticsearch (Analytics Cloud) Offline training of models EC2 docker Each container/process polls Elasticsearch for new data (No SQS/ Holds models SNS) 3 docker containers -Elasticsearch, Logstash, Kibana Docker containers, each assigned to individual CPU Holds "Anomalies" elasticsearch elastic 🗸 logstash ~15 channels per container/CPU instance used by application kıbana CPU processing totally independent **EBS Volume** Sends anomalies, "window" info to elasticsearch Holds instance on machine 2 EC2 docker Elasticsearch docker Index Machine 1 Machine 2

ML, processing

Soil Moisture Active Passive (SMAP)

- Routine operations
- Major radar failure
- ~4,000 telemetry channels
 - Power, CPU, RAM, Thermal, Radiation, counters
 - 14 command modules
 - 4B values
- Challenges
 - Semi-supervised
 - Complexity, diversity
 - Scale

